

PRODUCTS

I SCAN™ 2

Dual Iris Capture Scanner



Rapidly capture iris images for easy enrollment and foolproof identity verification.

Application Environments

- Military
- Border Control
- Law Enforcement

Cross Match® I Scan 2 enhances military and civilian security programs with fast and reliable biometric technology. A durable and compact dual iris capture scanner, I Scan 2 is an integral part of any comprehensive identity management program. With the system, organizations can extend their security installations by adding rapid mobile enrollment, identification and verification through iris capture applications. The USB-powered

handheld scanner is ANSI INCITS 379-2004 and ISO/IEC 19794-6 compliant — producing the highest quality iris images. And because it is standards-based, I Scan 2 is compatible with known iris matching algorithms and does not require a separate license to acquire and populate iris images.

The included I SCAN Essentials SDK and driver software enable image finding and stabilization, pupil segmentation, image quality assessment and auto capture functionality for quick and easy image collection. In the tradition of Cross Match livescan technology, I Scan 2 is the most advanced and easy-to-use iris capture solution on the market.

I SCAN™ 2

Features and Benefits

- Dual iris capture in less than ten seconds
- Automatic image capture without user intervention
- Durable housing
- Portable system that integrates into Cross Match Jump Kits or other mobile identity management solutions
- Fold open visor accurately sets optimum focus and shields the eyes from direct sunlight
- Operates in total darkness

Specifications

- Splash and dust resistant, designed to meet IP65 (IEC 60529)
- Shock per ISTA 2A Shipping and Handling Specification
- Vibration per ISTA 2A Shipping and Handling Specification
- Accommodates interpupillary distances (IPD) ranging from the 5th to the 95th percentile
- Meets iris image interchange format specifications: ANSI INCITS 379-2004 and ISO/IEC 19794-6 standards
 - Image quality high level
 - Spatial resolution: 4.0 lp/mm at 60% or higher contrast
 - Pixel Resolution: 16.7 pixels/mm (> 200 pixels over iris diameter of 9.5-13 mm)
- Incorporates "Anti-Dilation" system to facilitate a smaller pupil



- Near-IR Illumination (700-900 nm)
- Scanned FOV: 50 mm x 40 mm per eye
- Dual Optical system utilizing 1.3 megapixel cameras
- Certifications: FCC Class A, RoHS
- Certifications for Eye Safety: Class 1 LED Product IEC 60825-1:1993+A1:1997+A2:2001, ANSI RP-27.1-96
- Power supplied via USB cable on a USB 2.0-compliant port (no battery required)
- Cable ~ six-foot long, permanently attached with a strain-relief feature
- Device provides bitmap images at a maximum rate of 7.5 fps
- Housing:
 - PC/ABS blend
 - Attached visor to set optical distance
 - Retractable ambient light shield
- Standard depot maintenance
- Auto capture used as field calibration check
- Manufactured in U.S.

Dimensions and Environmental Conditions

Scanner Weight:

1.1 lbs (.5 kg)

Scanner Size:

6" x 1.9" x 6"
(152 mm x 48 mm x 152 mm)

Operating Temperature:

32° to 120°F (0°- 49° C)

Humidity Range:

10-90% non-condensing



I SCAN 2 captures iris images in less than ten seconds and weighs just over one pound.



Corporate Headquarters:

Cross Match Technologies, Inc.
3950 RCA Boulevard, Suite 5001
Palm Beach Gardens, FL 33410, USA
sales@crossmatch.com
customer@crossmatch.com
www.crossmatch.com

German Operations:

Cross Match Technologies GmbH
Unstrutweg 4
07743 Jena, Germany
international-sales@crossmatch.com
(Sales EMEA, Asia & Pacific)

Business Partner and System Integrator:

Media Technology Solution
Taman Harapan Baru Blok E5 No. 4 Bekasi - Indonesia
info@mtesolution.com
T: +62 21 8037 3834, 99652368 F: +62 21 8897 4589
www.mtesolution.com

Protecting People, Property and Privacy